

Banquet systems

Banquet trolleys, heated

Banquet trolleys, cooled





Banquet trolley BW 18

Banquet trolley, heated

Description

Structure

The banquet trolley is closed on all sides and is made entirely of CNS 18/10. The body and the door are double-walled and insulated. The cabinet is entirely sealed (hygiene version H2). All joints between the bottom and the walls have a corner radius ($R = 12 \text{ mm}$), so that the trolley can be sanitarily cleaned. The cabinet side walls are equipped with removable shelving frames for inserting grids. The distance between the grid supports is 115 or 75 mm. Its inherently stable chassis structure makes the trolley lightweight and at the same time very robust, so that it is perfectly suited for catering as well as in-house use.

The powerful convection heating is controlled via an electronic temperature control. A digital display indicates the set/actual temperatures. Heating may be wet or dry. A water reservoir with slosh baffle holds enough water to deliver steam for 5 to 6 h. The heating element can be taken out easily for cleaning. It is fixed by recesses in the trolley base. The banquet trolley is delivered ready to plug in with a 3 m power supply cord, shock-proof plug and cord reel. The hinged door has an all-round seal to keep maximum heat in. The double-walled hinged door can be opened to an angle of 270° . The central door lock with a recessed safety handle is self-engaging and locks at the trolley bottom and roof. The robust welded-in door hinge is extraordinarily stable and shock-protected, since it is hidden behind a shock protection strip.

Ergonomics

The banquet trolley has especially been designed for transporting plates, as well as for serving as a buffer station during special events such as banquets. The easily removable heating element can be used to provide the trolley interior with wet heat, so that the food on the plates does not dry out.

The four vertical trolley handles (2 on the left hand side and 2 on the right hand side of the trolley) guarantee

ergonomic steering. The opened door is kept securely between these handles, so that they can also be held when the door is open. The trolley has 4 corrosion-protected steering castors of 200 mm in diameter, 2 of them with brakes. An all-round, extra-wide, shock-absorbing grey plastic bumper rail protects the trolley from being damaged.

Technical data

Material:	CNS 18/10
Dims. of bumper rail:	70 x 38 mm
Temperature control:	continuous, from 30° to 85°C
Elec. connection:	230 V/50 Hz/1.5 kW
Standards:	CE compliant, spark-proof, VDE and GS tested; body: hygiene version H2, heating IP X1

Special features:	The interior can be heated with wet heat via an easily removable heating element. Interior in hygiene version H2. Digital temperature display.
-------------------	--

BW 18

Length:	763 mm
Width:	932 mm
Height:	1585 mm
Capacity:	9 x GN 2/1
Plate capacity	
Plate Ø:	24 cm: 45 pcs
	26 cm: 36 pcs
	28 cm: 27 pcs
	30 cm: 18 pcs
	31 cm: 18 pcs
Interval betw. supp. angles:	115 mm
Weight:	126 kg
Order No.:	566 392

BW 28

Length:	763 mm
Width:	932 mm
Height:	1585 mm
Capacity:	14 x GN 2/1
Plate capacity	
Plate Ø:	24 cm: 70 pcs
	26 cm: 56 pcs
	28 cm: 42 pcs
	30 cm: 28 pcs
	31 cm: 28 pcs
Interval betw. supp. angles:	75 mm
Weight:	134 kg
Order No.:	566 393

Banquet trolley, heated

BW 36

Length:	1316 mm
Width:	932 mm
Height:	1585 mm
Capacity:	9 x 1084 x 650 mm* 2 x 9 GN 2/1**

Plate capacity	*	**
Plate Ø: 24 cm:	90 pcs	90 pcs
26 cm:	72 pcs	72 pcs
28 cm:	63 pcs	54 pcs
30 cm:	54 pcs	36 pcs
31 cm:	54 pcs	36 pcs
Interval betw. supp. angles:	115 mm	
Weight:	196 kg	
Order No.:	566 394	

BW 56

Length:	1316 mm
Width:	932 mm
Height:	1585 mm
Capacity:	14 x 1084 x 650 mm* 2 x 14 GN 2/1**

Plate capacity	*	**
Plate Ø: 24 cm:	140 pcs	140 pcs
26 cm:	112 pcs	112 pcs
28 cm:	98 pcs	84 pcs
30 cm:	84 pcs	56 pcs
31 cm:	84 pcs	56 pcs
Interval betw. supp. angles:	75 mm	
Weight:	202 kg	
Order No.:	566 395	

*without dividing wall

**with dividing wall

Banquet trolley accessories

Plate carrier of CNS for transport of max. 8 plates of a max. diameter of 31 cm. The plate carriers can be placed directly onto the compartment's support angles. No grids required. For Model BW 36/56 the dividing wall is required.

Dimensions: 650 x 530 x 310 mm

	No. of plate carriers
BW 18/28	3 pcs
BW 36/56	6 pcs
BWK 4,5,6	3 pcs
Order No.:	566 653

Plate carrier of CNS for easy transport of portioned plates; max. 8 plates of up to 30 cm in diameter, without covers. Grids required in addition.

Dimensions: 660 x 330 x 330 mm

	No. of plate carriers	No. of grids
BW 18/28	3 pcs	3 pcs (650 x 530 mm)
BW 36/56	6 pcs	6 pcs (650 x 530 mm) w/ dividing wall
BW 36/56	9 pcs	3 pcs (1084 x 650 mm) w/o dividing wall
BWK 4,5,6	3 pcs	3 pcs (650 x 530 mm)

Order No.: 555 646

Plate carrier of CNS for easy transport of portioned plates; max. 10 plates of up to 30 cm in diameter, without covers. Grids required in addition.

Dimensions: 660 x 330 x 405 mm

	No. of plate carriers	No. of grids
BW 18/28	2 pcs	2 pcs (650 x 530 mm)
BW 36/56	4 pcs	4 pcs (650 x 530 mm) w/ dividing wall
BW 36/56	6 pcs	2 pcs (1084 x 650 mm) w/o dividing wall
BWK 4,5,6	2 pcs	2 pcs (650 x 530 mm)

Order No.: 555 647

Cover carrier of CNS; max. 8 plates of up to 30 cm in diameter, together with covers of up to 311 mm in diameter. Grids required in addition.

Dimensions: 660 x 330 x 320 mm

	No. of plate carriers	No. of grids
BW 18/28	3 pcs	3 pcs (650 x 530 mm)
BW 36/56	6 pcs	6 pcs (650 x 530 mm) w/ dividing wall
BW 36/56	9 pcs	3 pcs (1084 x 650 mm) w/o dividing wall
BWK 4,5,6	3 pcs	3 pcs (650 x 530 mm)

Order No.: 555 648

Banquet trolley, cooled

Description

Structure

The cooled banquet trolley is closed on all sides, double-walled and has an additional PUR foam insulation. To prevent heat from penetrating the trolley interior, the door is equipped with an additional seal, which means there are no contact surfaces via which heat transfer could take place.

In the upper part, the banquet trolley features an integrated refrigeration unit with convection blower as well as an automatic defrosting device. It is equipped with a digital display for temperature control from + 8°C to -12°C. An additional temperature control display is located at the door.

The compartment side walls are equipped with removable shelving frames for inserting grids. The distance between the grid supports is 115, 57.5 or 38.3 mm. This facilitates the cleaning of the trolley interior.

The electrical connection is located at the back of the trolley. It includes a 3 m power supply cord with shock-proof plug and cord reel. The non-projecting, robust door lock is self-engaging.

Ergonomics

There are two handles on the left hand side and two handles on the right hand side of the trolley.

The trolley has 4 corrosion-protected steering castors of 160 mm in diameter, 2 of them with brakes. An all-round, extra-wide, shock-absorbing plastic bumper rail protects the trolley from being damaged.

Technical data

Material:	CNS 18/10
Temperature control:	from +8°C to -12°C
Elec. connection:	230 V/50 Hz/0.775 kW
Standards:	CE, DIN 40050, splash-proof (IP X4)
Special features:	Additional integrated seal. Thermostatic temperature control from +8°C to -12°C. Temperature control display.

BWK 4

Length:	770 mm
Width:	845 mm
Height:	1830 mm
Weight:	142 kg
Interval betw. supp. angles:	115 mm
No. of supp. angles:	10 pcs
Capacity:	10 pcs GN 2/1 grids or GN containers
Plate capacity	
Plate Ø:	24 cm: 50 pcs
	26 cm: 40 pcs
	28 cm: 30 pcs
	30 cm: 20 pcs
	31 cm: 20 pcs
Order No.	555 638

BWK 5

Length:	770 mm
Width:	845 mm
Height:	1830 mm
Weight:	146 kg
Interval betw. supp. angles:	57.5 mm
No. of supp. angles:	20 pcs
Capacity:	20 pcs GN 2/1 grids or GN containers
Plate capacity	
Plate Ø:	24 cm: 100 pcs
	26 cm: 80 pcs
	28 cm: 60 pcs
	30 cm: 40 pcs
	31 cm: 40 pcs
Order No.	555 639

BWK 6

Length:	770 mm
Width:	845 mm
Height:	1830 mm
Weight:	150 kg
Interval betw. supp. angles:	38.3 mm
No. of supp. angles:	30 pcs
Capacity:	30 pcs GN 2/1 grids or GN containers
Plate capacity	
Plate Ø:	24 cm: 150 pcs
	26 cm: 120 pcs
	28 cm: 90 pcs
	30 cm: 60 pcs
	31 cm: 60 pcs
Order No.	555 640

For further accessories, such as dividing walls or grids, please refer to our price list.