

When you think Coffee Brewers . . .

think

Cecilware!



CECILWARE
Since 1911[®]

We Know What's Hot!

Coffee Station Series

- ✓ **High Performance** - 3.5 minute brew cycle with instant recovery.
- ✓ **Push Button Control** - Brew your favorite blend of coffee at the touch of a button.
- ✓ **Brew Light Indicator** - Lets the operator know that the coffee brewer is ready to brew.
- ✓ **High Limit Control** - Automatically turns the heater off if the brewer runs dry or overheats.
- ✓ **Precision Solid State Timers** - Standard in automatic brewers.
- ✓ **Polysulfone Water Tank** - Keeps liming to a minimum.
- ✓ **Liquid Level Control** - Automatically refills water tank at the end of each brew cycle.
- ✓ **12 Cup Capacity**
- ✓ **Unique Safe Guard Circuit** - Prevents possible flooding on water tap units.
- ✓ **All Stainless Steel Construction**
- ✓ **Easy To Service** - Components are easily accessible through the top.

Optional: Hot Water Faucet - for tea, hot chocolate, soup and more.

| Model # | Warmers | Height | Ship Weight |
|--|---------|---------|-------------|
| <i>Pourover Series</i> | | | |
| CS-2 | 2 | 22 1/2" | 25 lbs. |
| CS-3 | 3 | 23 3/4" | 26 lbs. |
| <i>Automatic Series</i> | | | |
| CS-2A | 2 | 24 1/4" | 28 lbs. |
| CS-3A | 3 | 24" | 28 lbs. |
| <i>Automatic Series with Hot Water Tap</i> | | | |
| CS-2AWT | 2 | 24 1/4" | 29 lbs. |
| CS-3AWT | 3 | 25 1/2" | 29 lbs. |

Electrical: 2 warmer units 120V, 1.6KW, 14A
3 warmer units 120V, 1.7KW, 15A
Line cord included

Plumbing: Automatic units require 1/4" water line
Dimensions: Width - 16" Depth - 9"

