



Model # H288

H288 Double Space Saver Oven Model & H288S One Standard Oven With Storage Base Model Specifications:

Gas medium duty range with (2) space saver ovens or (1) full size oven w/storage base (H288S) 48" (1219mm) wide. (8) open top Starfire burners with cast iron top and ring grates. Stainless steel front, sides, backguard and plate shelf. Available with optional hot top(s) and/or griddle. Recommended for churches, schools, cafes and small restaurants.



Standard Features:

- Cast iron top & ring grates
- 24,000 BTU / 7.03kW, (Natural Gas) or 20,000 BTU / 5.86kW, (Propane) Starfire burners, (8)
- Stainless steel front & two sides
- Stainless steel valve panel
- Stainless steel front rail
- Stainless steel backguard & plate shelf
- 25,000 BTU (7.37kw) oven burner
- Two space saver ovens; fully porcelain interior which includes oven bottom, top, rear, embossed sides, and inside door liner.
- One Full size oven, 30,000 BTU (8.79 kW) burner, with storage section (Model H288S)
- Removable nickel plated four position oven rack guides
- Nickel plated oven rack (one per oven)
- Heavy Duty "FDO" Oven Thermostat; 150° - 500°F (66°-260° C)
- 6" (152mm) Chrome steel legs with stainless steel inserts
- Gas pressure regulator
- One year limited warranty on parts & labor, (USA & Canada only)

Optional Features:

- Black porcelain top & ring grates, (change "H" in model number to "P")
- Stainless steel backguard/flue riser "BG"
- 10" (254mm) Low profile backguard - change "BG" to "LPBG"
- Celsius temperature dials
- Convection oven base (add suffix RC)
Note: Not available on space saver oven
- 12" hot top section; 3/8" (10mm) thick; (add suffix -1, -2, -3 or -4); standard on left or specify location
- 12", 24", 36" or 48" griddle (manual or thermostat control), 5/8" (19mm) thick, working depth 20-1/2" (521mm); standard on right or specify location
- Additional oven rack
- Stainless steel legs, set of (4)
- Set of (4) casters with front (2) locking

NOTE: Ranges supplied with casters must be installed with an approved restraining device.

<http://www.Garland-Group.com>

Garland Commercial Industries, Inc.
185 East South Street
Freeland, Pennsylvania 18224
Phone: (570) 636-1000
Fax: (570) 636-3903

Garland Commercial Ranges Ltd
1177 Kamato Road, Mississauga, Ontario
L4W 1X4 CANADA
Phone: 905-624-0260
Fax: 905-624-5669

Enodis UK LTD
Swallowfield Way, Hayes, Middlesex
UB3 1DQ ENGLAND
Telephone: 081-561-0433
Fax: 081-848-0041



Item #: _____
 Model: H288 & H288S
 Product Name: 48" Starfire Series
 Medium Duty Gas Range

Input Rating Per Burner (Natural Gas)										Operating Pressure "WC/mbar	
Open*		Hot Top**		Griddle***		Oven RC or Std.		Oven Space Saver/oven			
BTU	kW	BTU	kW	BTU	kW	BTU	kW	BTU	kW	Natural	Propane
24,000	7.03	18,000	5.27	18,000	5.27	30,000	8.78	25,000	7.32	4.5/11	10/25

Gas input ratings shown for installations up to 2000 ft., (610m), above sea level. Please specify altitudes over 2000 ft. Please specify gas type when ordering.

- * Two (2) burners per 12" (305mm) section, (rated at 20,000BTU/5.86kW with Propane)
- ** One (1) burner per optional 12" (305mm) section, (replaces 2 open burners); add suffix: -1, -2, -3 or -4 standard on left
- *** One (1) burner per 12" (305mm) of optional griddle width, (replaces 2 open burners); add suffix: -12G, -24G, -36G or -48G, (valve control)/-12TH, -24TH, -36TH or -48TH (thermostat control); standard on right

Exterior Dimensions			Oven Interior Dimensions			Installation Clearances	
Height w/shelf	Width	Depth	Height	Width ¹	Depth	Sides	Rear
59-1/2" (1511mm)	48" (1219mm)	33" (838mm)	13-1/2" (343mm)	20-1/4" (514mm)	22" (559mm)	6" (152mm)	6" (152mm)

¹ Space Saver Oven width, standard oven width 26-14" (667mm)

NOTE: Installation clearance reductions are applicable only where local codes permit.

This product is not approved for residential use.

Model	Shipping Wt.		Entry Clearances	
	Lbs.	Kg	Crated	Uncrated
H288	700	318	46" (1168mm)	34" (864mm)
H288S	550	249	46" (1168mm)	34" (864mm)
H288RC	750	340	46" (1168mm)	39" (991mm)

Installation notes: For RC oven add 5" (127mm) to overall depth. Electric characteristics each RC oven: 1/3 HP motor; 120VAC, Single phase, 3.4 Amps (6 Ft /1829mm power supply cord provided.)

